



# Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

### Engine and cooling system Regata 100Sie & Weekend 1986 to 1988

Type		149 C3.000 DOHC
Capacity (cm <sup>3</sup> ) / number of cylinders		1585 / 4
Compression ratio / pressure	bar	9.7 / _
Oil pressure	bar	[3.4 to 4.9]
Oil temperature	°C	100
Valve clearance - inlet	mm	0.45±0.04
Valve clearance - exhaust	mm	0.50±0.04
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	81 to 85
Radiator cap pressure	bar	1.0

### Fuel system Regata 100Sie & Weekend 1986 to 1988

Idle speed - manual [auto]	rpm	850±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	1.5±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO <sub>2</sub> @ idle speed [3000 rpm] - see page VI	%	_
O <sub>2</sub> @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		GM/Fiat
Type / ref		Delco SPI
Main jet / needle		_
Injection pressure	bar	_
Pump pressure	bar	_
Octane rating	RON	95[L]

### Ignition system Regata 100Sie & Weekend 1986 to 1988

Type		AEI
Ignition coil		Marelli
Primary resistance	ohms	0.31 to 0.38
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Marelli
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	10±2 BTDC @ 850±50
V = Vacuum NV = No Vacuum		_
Total ignition advance	° Crankshaft @ rpm	10±2 @ 700 to 1200
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	40±2 @ 3200 to 6500
Centrifugal check.	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	_
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Bosch/Champion
Type		WR7DC / RN9YC
Electrode gap	mm	0.70 to 0.80

### Electrical system Regata 100Sie & Weekend 1986 to 1988

Battery	V / CC / RC	12 / 210 / 65
Alternator voltage / full load current / engine rpm		14.0 to 14.3 / _ / 3500
Starter motor current / voltage - cranking	A / V	270 / 9.2
- locked	A / V	540 / 6.5

### Running gear Regata 100Sie & Weekend 1986 to 1988

<b>Brakes -</b>		
Front (min. friction material thickness)	mm	1.5
Rear (min. friction material thickness)	mm	1.5

<b>Tyres</b>		
Saloon	Size	165/65x14
Estate / Van	Size	165/65x14
Pressure - front / rear - Saloon	bar	2.2 / 2.2
- Estate / Van	bar	2.2 / 2.2

### Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-1.0 to +1.0
Camber		+1° to 2°
Castor		+1° to 2°
King pin inclination		_

### Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	0 to +4.0 <sup>1</sup>
Camber		-45' to +15' <sup>2</sup>

### Torque wrench settings Regata 100Sie & Weekend 1986 to 1988

Cylinder head - stage 1	Nm	20
- stage 2	Nm	40
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	51
Main bearings	Nm	20 + 80°
Clutch cover	Nm	16
Flywheel [driveplate]	Nm	83
Front hubs	Nm	294 staked
Rear hubs	Nm	216staked
Wheel nuts / bolts	Nm	86
Spark plugs	Nm	25 to 30

### Capacities Regata 100Sie & Weekend 1986 to 1988


Engine oil & filter	litres	4.6
Gearbox - 4-speed [5-speed]	litres	2.9
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	7.5
Fuel tank	litres	55

### Notes and Illustrations


<sup>1</sup>Weekend: +2.0 to 6.0

<sup>2</sup>Weekend: -40' to +20'


1: Idle speed 2: CO / Mixture



1585 cm<sup>3</sup>, DOHC



Delco SPI



Delco SPI